



PIN	FUNCTION
A	+15 VDC INPUT
B	SIGNAL PWR & GND
C	-15 VDC INPUT
D	E <sub>o</sub> VOLTAGE OUTPUT
E	FACTORY TEST RETURN
F	FACTORY TEST

NOTES:

1. ANGULAR ACCELERATION IN DIRECTION OF ARROW PRODUCES POSITIVE OUTPUT.
2. MS3113H-10-6P RECEPTACLE OR EQUIV. LESS SEAL.
3. NAMEPLATE CONTAINS THE FOLLOWING DATA:

+ ←  
ACCELEROMETER  
ASXC -  
PN:  
SN: XXXX REV.

APPLICATION		DIMENSIONS ARE IN INCHES AND APPLY TO PART BEFORE FINISHING			TITLE	
USED ON	NEXT ASSY	TOLERANCE UNLESS SPECIFIED			OUTLINE ANGULAR ACCLRM ASXC SERIES	
		TWO PLACE DECIMALS    (.00) ± .01 THREE PLACE DECIMALS (.000) ± .005 ANGLES                     ± 1° RAW MATL - COMMERCIAL STANDARD				
					DRAWING NO.  OD0255267-000	
				MANCHESTER, NH TRIPLETT MODUTEC A&M EMICO		
				PROPRIETARY NOTICE THIS DRAWING IS THE PROPERTY OF JEWELL INSTRUMENTS, LLC. NEITHER THIS DOCUMENT NOR THE DATA CONTAINED HEREIN SHALL BE DISCLOSED, REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN AUTHORIZATION OF JEWELL INSTRUMENTS, LLC. NO RIGHT IS GRANTED TO DISCLOSE OR SO USE ANY INFORMATION CONTAINED HEREIN. ALL RIGHTS RESERVED.		
				SCALE 1:1	CAGE CODE 33005	SHEET 1 OF 1