

AC184-M12A Series

Multipurpose Accelerometer, Side Exit M12 Connector, M8x1.25 Captive Bolt, 100 mV/g, ±10%



VIBRATION ANALYSIS HARDWARE




Product Features

Perfect for M8 Mounting Applications
High Performance in a Low Cost Sensor

- ▶ 100 mV/g Sensitivity, ± 10%
- ▶ ± 80 g, peak Dynamic Range

AC184-M12A 4 Pin Connector

Connector Pin	Polarity
Pin 1	(+) Signal/Power
Pin 2	(-) Common
Pin 3	Not Used
Pin 4	Not Used



Stock Product

Specifications	Standard	Metric	Specifications	Standard	Metric
Sensitivity (±10%)		100 mV/g	Environmental		
Frequency Response (±3dB)	30-600,000 CPM	0,5-10000	Operating Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±10%)	120-300,000 CPM	2,0-5000 Hz	Maximum Shock Protection		5,000 g, peak
Dynamic Range		± 80 g, peak *Vsource ≥ 22V, 12Vbias	Electromagnetic Sensitivity		CE
Electrical			Sealing		Welded, Hermetic
Settling Time	<2.5 seconds		Submersible Depth	200 ft.	60 m
Voltage Source (IEPE)	18-30 VDC		SIL Rating		SIL 2
Constant Current Excitation	2-10 mA		Physical		
Spectral Noise @ 10 Hz	14 µg/√Hz		Sensing Element		PZT Ceramic
Spectral Noise @ 100 Hz	2.3 µg/√Hz		Sensing Structure		Shear Mode
Spectral Noise @ 1000 Hz	2 µg/√Hz		Weight	6 oz	170 grams
Output Impedance	<100 ohm		Case Material		316L Stainless Steel
Bias Output Voltage	10-14 VDC		Mounting Thread		M8x1.25
Case Isolation	>10 ⁸ ohm		Connector (Non-Integral)		2 Pin MIL-C-5015
			Resonant Frequency	1,200,000 CPM	20000 Hz
				2 to 5 ft.	2.7 to