

# AC240 Series

Premium Miniature Industrial Accelerometer, High Frequency, Top Exit 2 Pin Mini-MIL Connector, 100 mV/g, ±5%



VIBRATION ANALYSIS HARDWARE




## Product Features

High Resonant Frequency with Excellent Frequency Response

- ▶ 1,500,000 CPM max frequency response
- ▶ 34 kHz Resonant Frequency
- ▶ 100 mV/g ± 5% Sensitivity

### AC240-1D 2 Pin Mini Mil Connector


Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common



Stock Product

### AC240-2D CB110 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

### AC240-3D CB206 Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

### AC240-6D CB611 Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC240	M/ or M8/AC240	<b>Environmental</b>		
Sensitivity (±5%)	100 mV/g		Operating Temperature Range	-58 to 250 °F	-50 to 121 °C
Frequency Response (±3dB)	36-1,500,000 CPM	0.6-25000 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response (±10%)	60-720,000 CPM	1,0-12000 Hz	Electromagnetic Sensitivity	CE	
Frequency Response (±5%)	120-480,000 CPM	2-8000 Hz	Sealing	Welded, Hermetic	
Dynamic Range	± 80 g, peak *Vsource ≥ 22V, 12Vbias		Submersible Depth	200 ft.	60 m
<b>Electrical</b>			SIL Rating	SIL 2	
Settling Time	<2.5 Seconds		<b>Physical</b>		
Voltage Source (IEPE)	18-30 VDC		Sensing Element	PZT Ceramic	
Constant Current Excitation	2-10 mA		Sensing Structure	Shear Mode	
Spectral Noise @ 10 Hz	30 µg/√Hz		Weight	0.7 oz	20 grams
Spectral Noise @ 100 Hz	4 µg/√Hz		Case Material	316L Stainless Steel	
Spectral Noise @ 1000 Hz	2 µg/√Hz		Mounting Thread	1/4-28 Blind Tapped Hole	
Output Impedance	<100 ohm		Connector (Non-Integral)	mini-MIL	