



Dew point and temperature probe DMP5
For dew point measurement in high temperatures up to 180 °C

				Probe head and cable	Probe cable	Sensor type	Filter type	Operating pressure	Baud rate	Parity, data bit, stop bit	Probe Modbus address	Reserved	Probe mounting accessory	Connection cable
				DMPX	5	1	A	0			0			
1	Probe head and cable DMP5 for high temperatures			5										
2	Probe cable 2m cable 10m cable				A B									
3	Sensor type DrycapS					1								
4	Filter type Sintered stainless steel filter						A							
5	Operating pressure Setting for ppm and other calculated variables 1) 1 bar (absolute)							0						
6	Baud rate 1) 19200 use with Indigo transmitters 9600								A B					
7	Parity, data bit, stop bit 1) 8,N,2 use with Indigo transmitters 8,E,1 8,O,1									0 2 4				
8	Probe Modbus address 1) 240 use with Indigo transmitters 110 120 130 140										A B C D E			
9	Reserved None											0		
10	Probe mounting accessory None (installation into existing mounting flange) Mounting flange												0 A	
11	Connection cable None 1,5m, open ends 10m, open ends													0 1 2

1) Factory pre-set, can be changed in the field with a service cable (P/N 242659)

Probe can be connected to INDIGO series of transmitters regardless of the output configuration.

Selections in bold are included in the prices of the basic versions.

Selections in *italic* are available at an extra price.

Example of order code with typical settings:

For use with INDIGO transmitters	DMPX	5	A	1	A	0	A	0	A	0	A	0	A	0
For use with Modbus RTU	DMPX	5	A	1	A	0	A	0	A	0	A	0	A	2

Valid from: October 2022