

UP55G-600F-HD-D0

Thermal detector for laser power measurement up to 600 W.



PRODUCT FAMILY KEY FEATURES

HIGH DENSITY ABSORBER

The HD absorber is the strongest on the market for use at high powers, presenting both high average power handling and high power density capabilities

NO NEED FOR WATER-COOLING

Unique on the market, measure 600 W of continuous power without the need for water-cooling. Just plug the fan and you are ready to go!

SMART INTERFACE

Containing all the calibration data

COMPATIBLE STAND

[STAND-S-443-C](#)

SPECIFICATIONS

MEASUREMENT CAPABILITIES

Maximum average power (continuous)	600 W
Maximum average power (1 minute)	600 W
Noise equivalent power ¹	45 mW
Spectral range ²	0.193 - 20 μm
Typical rise time ³	5 s
Power calibration uncertainty ⁴	$\pm 2.5\%$
Repeatability	$\pm 0.5\%$

1. Nominal value, actual value depends on electrical noise in the measurement system.

2. For the calibrated spectral range, see the user manual.

3. With anticipation.

4. Including linearity with power.

MEASUREMENT CAPABILITIES (ENERGY MODE)

Maximum measurable energy ¹	200 J
Noise equivalent energy ²	0.25 J
Minimum repetition period	12 s
Maximum pulse width	430 ms
Energy calibration uncertainty ³	$\pm 5\%$

1. For 360 μs pulses. Higher pulse energy possible for long pulses (ms), less for short pulses (ns).

2. Nominal value, actual value depends on electrical noise in the measurement system.

3. When single-shot energy calibration is purchased

DAMAGE THRESHOLDS

Maximum average power density ¹	45 kW/cm ²
Maximum energy density ²	1 J/cm ²

1. At 1064 nm, 10 W CW. May vary with wavelength and average power.

2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

PHYSICAL CHARACTERISTICS

Cooling	Fan
---------	-----

Aperture diameter	55 mm
Absorber	HD
Dimensions	120H x 120W x 135D mm
Weight	2.75 kg

ORDERING INFORMATION

UP55G-600F-HD-D0	201878B
UP55G-600F-HD-IDR-D0	205134
UP55G-600F-HD-BLU-D0	203721B
UP55G-600F-HD-INT-D0	203197B

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us